## NSN 4820-00-903-8360

Safety Relief Valve - Page 1 of 2

Thread Class: 3b 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-903-8360

Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
6.0 gallons per minute
Maximum Operating Temp:
280.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
16 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
2000.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.500 inches 1st end
Material:
Stainless steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 4820-00-903-8360

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0