## NSN 4820-00-904-2302



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-904-2302 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 260.0 degrees fahrenheit 2nd response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 100.0 pounds per square inch 2nd response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees all ends **Special Features:** The end connection identified bove as the second end is the valve inlet Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6 assn standard single material response Media For Which Designed: Alcohol, ethyl 2nd response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** 

N/a

Unf all ends Shelf Life:

## NSN 4820-00-904-2302

Check Valve - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.