NSN 4820-00-905-2468

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-905-2468 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 7.0 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Valve stem lock shield and pressure tight outlet side **Adjustable Pressure Range:** +100.0/+1000.0 pounds per square inch **Maximum Operating Pressure:** 265.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends **Outside Diameter Tube Accommodated:** 0.375 inches all ends Material: Stainless steel seat Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-905-2468

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0