NSN 4820-00-907-7255

Shuttle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-907-7255 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Piston Valve Discharge Flow Rate: 1.2 gallons per minute **Maximum Operating Temp:** 180.0 degrees fahrenheit 2nd response **Connection Style:** G4 gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Mounting Facility: Bracket Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.438 inches 1st end **Special Features:** Third fluid end accommodates 0.438 in. Diameter bolt, fluid passage Material: Rubber synthetic packing Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Enamel **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unf all ends Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4820-00-907-7255

Shuttle Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.