NSN 4820-00-909-0470

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-909-0470

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+1420.0/+1520.0 pounds per square inch
Opening Pressure Setting:
1470.0 pounds per square inch
Outside Diameter:
9.625 inches 1st end
Thickness:
1.688 inches 1st end
Bolt Hole Diameter:
1.125 inches 1st end
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
6.188 inches 2nd end
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-909-0470

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0