NSN 4820-00-912-3555

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-912-3555

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield and bonnet packing
Maximum Operating Pressure:
350.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
165.0 pounds per square inch
Material:
Stainless steel stem
Material Specification:
Qq-b-626, alloy 360 federal specification single material response body
Media For Which Designed:
Air single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-912-3555

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0