NSN 4820-00-912-8008

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-912-8008

Thread Direction: Right-hand all ends Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure: 6000.0 pounds per square inch single response							
Right-hand all ends Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Poppet Disk Loading Method: Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Disk Loading Method: Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Spring Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Maximum Operating Temp: 200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
200.0 degrees fahrenheit single response Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Connection Style: Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Gasket seal (boss) 1st end Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Valve Operation Method: Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Automatic Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Connection Type: Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Threaded internal boss all ends Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Mounting Position: Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Horizontal or vertical Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
Thready Qty Per Inch (tpi): 12 all ends Maximum Operating Pressure:							
12 all ends Maximum Operating Pressure:							
Maximum Operating Pressure:							
6000.0 pounds per square inch single response							
Thread Size:							
1.500 inches all ends							
Outside Diameter Tube Accommodated:							
0.750 inches 1st end							
Material:							
Aluminum alloy 2024 body							
Material Specification:							
Qq-a-225/6, alloy 2024, t4 federal specification 2nd material response seat							
Media For Which Designed:							
Water-oil-gas single response							
Surface Treatment:							
Anodize							
Surface Treatment Specification:							
Mil-a-8625, type 2 military specification single treatment response							
Style Designator:							
Straight thru							
Thread Series Designator:							
Un all ends							
Shelf Life:							
N/a							

NSN 4820-00-912-8008

Check Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.