NSN 4820-00-913-2754

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-913-2754

Pipe Size Accommodated:

0.125 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

-40.0 degrees fahrenheit 1st response250.0 degrees fahrenheit 2nd response

Connection Style:

G46b plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.125 inches 1st end

Opening Pressure Setting:

11.0 pounds per square inch

Special Features:

Pop-off type

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6, alloy2024, t4 federal specification single material response seat

Media For Which Designed:

Hydrogen 5th response

Surface Treatment:

Anodize

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-913-2754

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

