## NSN 4820-00-913-2754

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-913-2754

Pipe Size Accommodated:
0.125 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
-40.0 degrees fahrenheit 1st response250.0 degrees fahrenheit 2nd response
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches 1st end
Opening Pressure Setting:
11.0 pounds per square inch
Special Features:
Pop-off type
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024, t4 federal specification single material response seat
Media For Which Designed:
Hydrogen 5th response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-913-2754

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0