NSN 4820-00-913-6945

Check Valve - Page 1 of 2

Thread Class: 3a 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-913-6945

| Thread Direction: |
|---|
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 275.0 degrees fahrenheit single response |
| Connection Style: |
| Gasket seal compression (tube) 2nd end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube 2nd end |
| Mounting Facility: |
| Bulkhead |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 18 2nd end |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch single response |
| Thread Size: |
| 0.875 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outside Diameter Tube Accommodated: |
| 0.625 inches 1st end |
| Material: |
| Aluminum alloy seat |
| Media For Which Designed: |
| Hydraulic fluid, mineral base single response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| |

NSN 4820-00-913-6945

Check Valve - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A530b0