

View Online at <https://aerobasegroup.com/nsn/4820-00-913-9282>

Flow Control Device:

Disk

Bolt Hole Quantity:

24 all ends

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Maximum Operating Pressure:

250.0 pounds per square inch single response

Outside Diameter:

30.500 inches all ends

Face To Face Distance:

40.000 inches

Thickness:

2.500 inches all ends

Bolt Hole Diameter:

1.375 inches all ends

Bolt Circle Diameter:

27.000 inches all ends

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

27.250 inches 1st end

Special Features:

W/two bosses on one side, drilled and tapped 1/2-14 npt thd, and equipped w/hexhead steel pipe plugs

Material:

Rubber butadiene-acrylonitrile class nbr flow control device and iron cast flow control device

Material Specification:

Mil-p-5315 military specification single material response flow control device

Media For Which Designed:

Propane 3rd response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-t-704, type a military specification single treatment response

Style Designator:

Straight thru

Furnished Items And Quantity:

2 plugged drain

Specification Or Standard:

250 class and 20 size

Departure From Cited Document:

As modified by drilled bosses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0

Mil-std (military Standard):

Mil-p-5315 spec.