NSN 4820-00-915-1469

Angle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-915-1469
Pipe Size Accommodated:
1.500 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Welded
Maximum Operating Temp:
975.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Material:
Stainless steel stem
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Test Data Document:
81349-mil-v-22094 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
B composition
Departure From Cited Designator:
As differentiated by quality control in accordance with navships 0948-045-7010 material identification and control instructions for level
1/sub-safe items
Reference Number Differentiating Characteristics:
Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items
Shelf Life:
N/a
Unit Of Measure:

Vec - demil/mli

Demilitarization:

NSN 4820-00-915-1469 Angle Valve - Page 2 of 2



Fiig:

A046b0