## NSN 4820-00-917-0556

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-917-0556

| Pipe Size Accommodated:                                      |
|--|
| 1.000 inches all ends  |
| Thread Direction:  |
| Right-hand all ends  |
| Flow Control Device:   |
| Disk   |
| Bonnet Type:   |
| Outside screw-yoke   |
| Bonnet Attachment Method:                                    |
| Bolted   |
| Renewable Seat Ring Type:                                    |
| Threaded   |
| Maximum Operating Temp:                                      |
| 850.0 degrees fahrenheit 4th response                        |
| Connection Style:  |
| G9 plain, optional en (pipe) all ends                        |
| Valve Operation Method:                                      |
| Manual   |
| Connection Type:   |
| Threaded internal pipe all ends                              |
| Features Provided:   |
| Bonnet packing   |
| Thready Qty Per Inch (tpi):                                  |
| 11-1/2 all ends  |
| Maximum Operating Pressure:                                  |
| 1000.0 pounds per square inch 4th response                   |
| Thread Size:   |
| 1.000 inches all ends  |
| Material:  |
| Steel uns k03504 packing                                     |
| Material Specification:                                      |
| Astm a182, gr f6 assn standard single material response seat |
| Media For Which Designed:                                    |
| Propane 4th response   |
| Style Designator:  |
| Err-090  |
| Thread Series Designator:                                    |
| Npt all ends   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 4820-00-917-0556

Globe Valve - Page 2 of 2



| Demi |  |  |  |
|------|--|--|--|
|      |  |  |  |
|      |  |  |  |

No

Fiig:

A046b0