

View Online at <https://aerobasegroup.com/nsn/4820-00-920-3623>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Connection Style:

G50 external seat for gasket seal (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external boss 1st end

Features Provided:

Bonnet packing

Adjustable Pressure Range:

+5.0/+10.0 pounds per square inch

Maximum Operating Pressure:

50.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Stainless steel seat

Material Specification:

Mil-r-25897, type2, class 1 military specification 2nd material response flow control device

Media For Which Designed:

Oil, lubricating, diester base 3rd response

Style Designator:

Err-090

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-25897 spec.