

View Online at <https://aerobasegroup.com/nsn/4820-00-922-5931>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Threaded

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

3.000 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Criticality Code Justification:

Zzzy

Outside Diameter:

8.250 inches 1st end

Face To Face Distance:

14.000 inches

Thickness:

1.250 inches 1st end

Bolt Hole Diameter:

0.875 inches 1st end

Bolt Circle Diameter:

6.625 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

5.000 inches 1st end

Material:

Steel uns j03008 body

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0