NSN 4820-00-923-4432



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-923-4432 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 10.0 gallons per minute **Maximum Operating Temp:** 165.0 degrees fahrenheit single response **Connection Style:** G5a flar (tube) 1st end **Connection Type:** Threaded internal boss 1st end **Maximum Operating Pressure:** 300.0 pounds per square inch single response **Thread Size:** 0.563 inches 1st end **Opening Pressure Setting:** 250.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.563 inches 1st end Media For Which Designed: Hydraulic fluid, petroleum base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Err-090 **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A046b0

NSN 4820-00-923-4432

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.