NSN 4820-00-925-0708

Ball Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-925-0708

| Pipe Size Accommodated: |
|--------------------------------------------------------------------------------------------------------------|
| 3.000 inches 1st end |
| Bonnet Type: |
| Packing retaining |
| Renewable Seat Ring Type: |
| Pressed-in |
| Connection Style: |
| Streamlined with one brazing ring 1st end |
| Valve Operation Method: |
| Hydraulic |
| Connection Type: |
| Unthreaded internal pipe 1st end |
| Power Drive Operating Pressure: |
| 900.0 pounds per square inch |
| Maximum Operating Pressure: |
| 650.0 pounds per square inch single response |
| Criticality Code Justification: |
| Zzzy |
| Material: |
| Titanium alloy uns r56400 flow control device |
| Media For Which Designed: |
| Water, salt single response |
| Style Designator: |
| A1 straight thru |
| Reference Number Differentiating Characteristics: |
| Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A046b0 |
| |
| |