## NSN 4820-00-926-4215

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-926-4215

| Pipe Size Accommodated:   |
|---|
| 0.750 inches 1st end  |
| Flow Control Device:  |
| Disk  |
| Bonnet Type:  |
| Inside screw  |
| Bonnet Attachment Method:   |
| Threaded  |
| Maximum Operating Temp:   |
| 150.0 degrees fahrenheit single response  |
| Connection Style:   |
| Socket with brazing ring 1st end  |
| Valve Operation Method:   |
| Manual  |
| Connection Type:  |
| Unthreaded internal pipe 1st end  |
| Maximum Operating Pressure:   |
| 700.0 pounds per square inch single response  |
| Criticality Code Justification:   |
| Zzzy  |
| Material:   |
| Nickel alloy stem   |
| Media For Which Designed:   |
| Water-oil-gas single response   |
| Style Designator:   |
| Err-090   |
| Reference Number Differentiating Characteristics:   |
| Material controlled iaw navsea 0948-lp-045-7010 material control standard for level i items |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| A046b0  |
|   |
|   |