## NSN 4820-00-932-0938

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Poppet

N/a

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-00-932-0938

Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+1290.0/+1375.0 pounds per square inch
Opening Pressure Setting:
1300.0 pounds per square inch
Outside Diameter:
7.500 inches 2nd end
Thickness:
1.250 inches 1st end
Bolt Hole Diameter:
1.125 inches 1st end
Bolt Circle Diameter:
5.875 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.875 inches 1st end
Material:
Stainless steel seat
Style Designator:
Err-090
Shelf Life:

## NSN 4820-00-932-0938

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0