

View Online at <https://aerobasegroup.com/nsn/4820-00-935-5563>

Pipe Size Accommodated:

0.250 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

G9 plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

18 1st end

Adjustable Pressure Range:

+430.0/+650.0 pounds per square inch

Maximum Operating Pressure:

650.0 pounds per square inch single response

Thread Size:

0.250 inches 2nd end

Opening Pressure Setting:

550.0 pounds per square inch

Material:

Stainless steel flow control device or plastic polytetrafluoroethylene flow control device

Media For Which Designed:

Air 1st response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.