NSN 4820-00-935-9339

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-935-9339

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Valve stem lock shield and bonnet packing and pressure tight outlet side
Maximum Operating Pressure:
100.0 pounds per square inch 1st response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
410.0 pounds per square inch
Material:
Stainless steel seat
Media For Which Designed:
Gas, natural 1st response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-00-935-9339

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0