## NSN 4820-00-936-9166



Restrictor Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-936-9166 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Connection Style:** Flared (tube) 1st end **Connection Type:** Threaded external tube 1st end **Mounting Position:** Horizontal Thready Qty Per Inch (tpi):

20 1st end

**Maximum Operating Pressure:** 

3000.0 pounds per square inch single response

**Thread Size:** 

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:** 

0.250 inches 1st end

**Special Features:** 

2.220 in. Lg over-all, 0.688 in. Across flats

Material:

Stainless steel flow control device

Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

**Surface Treatment:** 

**Passivate** 

**Style Designator:** 

Straight thru

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 4820-00-936-9166

Restrictor Check Valve - Page 2 of 2



Fiig:

A530b0