NSN 4820-00-938-7470

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-938-7470

Body Material: Aluminum alloy, qq-a-601, alloy 356, temper t6 **Outside Surface Treatment:** Anodized **Body Style:** Straight thru Stem Material: Aluminum alloy, qq-a-200/3, alloy 2024, t4 **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 7/16-20 unif **First End Thread Class:** 3b First End Thread Direction: Right-hand Second End Relationship With First End: Identical **Seat Material:** Aluminum alloy, qq-a-200/3, alloy 2024, t4 **Packing Material:** Rubber, buna-n **Flow Control Device:** Piston, weighted type Flow Control Device Material: Aluminum alloy, qq-a-200/3, alloy 2024, t4 **End Connection Quantity:** 2 Renewable Seat Ring Type: Pressed-in **Regulation Type:** Manual single stage **Manual Control Method:** Screw Valve Loading Method: Spring **Maximum Inlet Pressure Rating:**

1000.0 pounds per square inch

Outlet Pressure Setting:

23.0 pounds per square inch

NSN 4820-00-938-7470

Fiig: A21100

Fluid Pressure Regulating Valve - Page 2 of 2



Outlet Pressure Accuracy Rating:
1.000 pounds per square inch
Filter:
Not included
Tempurature Rating:
Between -61.0 degrees fahrenheit and 150.0 degrees fahrenheit
Supplementary Features:
Appl to acft, type c-130/apq 122
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No