

View Online at <https://aerobasegroup.com/nsn/4820-00-939-7929>

Pipe Size Accommodated:

1.500 inches 1st end

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Welded

Maximum Operating Temp:

775.0 degrees fahrenheit single response

Connection Style:

Socket err-100

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Criticality Code Justification:

Zzzx

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Test Data Document:

81349-mil-v-22094 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Or Standard:

N composition

Departure From Cited Designator:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0