## NSN 4820-00-943-3885

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-943-3885
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Seat Angle:
12.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Special Features:
Rated for 3.0 gpm flow
Material:
Stainless steel seat
Media For Which Designed:
Air 1st response
Style Designator:
Straight thru
Test Data Document:
97403-13207e2639 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unf all ends
Shelf Life:
N/a

## NSN 4820-00-943-3885

Check Valve - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A530b0