

View Online at <https://aerobasegroup.com/nsn/4820-00-945-9308>

Thread Class:

3b all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Pressure seal, ring type

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

3000.0 degrees fahrenheit single response

Connection Style:

Flare (tube) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal tube all ends

Mounting Facility:

Threaded fastener

Mounting Position:

Horizontal

Features Provided:

Valve stem lock shield

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches all ends

Outside Diameter Tube Accommodated:

0.250 inches all ends

Material:

Stainless steel stem

Material Specification:

Qq-a-225/6, alloy 2024 federal specification single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Enamel

Style Designator:

Straight thru

Test Data Document:

70236-t1175 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0