NSN 4820-00-947-3562

Safety Relief Valve - Page 1 of 2

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-947-3562

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
End Application:
Helicopter, iroquois uh-1
Connection Style:
G5a flar (tube) 1st end
Valve Operation Method:
Hydraulic
Connection Type:
Threaded internal tube 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+1000.0/+2300.0 pounds per square inch
Maximum Operating Pressure:
1265.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Criticality Code Justification:
Feat
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Special Features:
Weapon system essential
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Err-090
Thread Series Designator:
Unf 1st end

NSN 4820-00-947-3562

Safety Relief Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0