## NSN 4820-00-950-2782

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-950-2782

Pipe Size Accommodated:
0.375 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Pressure seal, ring type
Disk Loading Method:
Spring
Connection Style:
G46b plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Valve stem lock shield and pressure tight outlet side  Thread Size:
Thread Size:
Thread Size: 0.500 inches 1st end
Thread Size: 0.500 inches 1st end Seat Angle:
Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end
Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Opening Pressure Setting:
Thread Size: 0.500 inches 1st end Seat Angle: 45.0 degrees 1st end Opening Pressure Setting: 300.0 pounds per square inch
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body  Style Designator:
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body  Style Designator:  Err-090
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body  Style Designator:  Err-090  Thread Series Designator:
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body  Style Designator:  Err-090  Thread Series Designator:  Unf 1st end
Thread Size:  0.500 inches 1st end  Seat Angle:  45.0 degrees 1st end  Opening Pressure Setting:  300.0 pounds per square inch  Outside Diameter Tube Accommodated:  0.312 inches 1st end  Material:  Copper alloy body  Style Designator:  Err-090  Thread Series Designator:  Unf 1st end  Shelf Life:

No

Demilitarization:

## NSN 4820-00-950-2782

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0