NCN 1000 00 050 0506



NSN 4820-00-950-9506
Check Valve - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4820-00-950-9506
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Facility:
Bulkhead
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, alloy 2024, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf all ends

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-950-9506

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.

