## NSN 4820-00-953-1970

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-953-1970

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
G46b plain (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe all ends
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches all ends
Opening Pressure Setting:
21.0 pounds per square inch
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device
Media For Which Designed:
Oil, chlorinated transformer 2nd response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

## NSN 4820-00-953-1970

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.