NSN 4820-00-953-1970

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-953-1970

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Connection Style:

G46b plain (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe all ends

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.125 inches all ends

Opening Pressure Setting:

21.0 pounds per square inch

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device

Media For Which Designed:

Oil, chlorinated transformer 2nd response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

NSN 4820-00-953-1970

Safety Relief Valve - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

