

View Online at <https://aerobasegroup.com/nsn/4820-00-953-5684>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Connection Style:

Gasket seal (boss) 1st end

Connection Type:

Threaded internal boss 1st end

Mounting Position:

Horizontal or vertical

Features Provided:

Valve stem lock shield and bonnet packing

Thready Qty Per Inch (tpi):

20 1st end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Special Features:

74.0 degrees operating range

Media For Which Designed:

Hydraulic fluid, petroleum base single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military standard single treatment response

Style Designator:

Straight thru

Test Data Document:

76301-32-691550 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.