NSN 4820-00-953-5685

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-953-5685

Inread Class:
3b 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Connection Style:
Plain, optional end (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal tube 1st end
Mounting Facility:
Threaded fastener
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military standard single treatment response
Style Designator:
Straight thru
Test Data Document:
70236-t1176 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-953-5685

Lift-check Valve - Page 2 of 2



Demi			

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.