NSN 4820-00-953-5685

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-953-5685

| Inread Class: |
|--|
| 3b 1st end |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain, optional end (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded internal tube 1st end |
| Mounting Facility: |
| Threaded fastener |
| Mounting Position: |
| Horizontal |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.437 inches 1st end |
| Outside Diameter Tube Accommodated: |
| 0.250 inches 1st end |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 military standard single treatment response |
| Style Designator: |
| Straight thru |
| Test Data Document: |
| 70236-t1176 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 4820-00-953-5685

Lift-check Valve - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

Yes - demil/mli

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.