## NSN 4820-00-953-9258



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-953-9258 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 180.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 600.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 37.0 degrees all ends **Special Features:** First end bulkhead type per ms33657 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, alloy 2024, t4 federal specification single material response Media For Which Designed: Carbon dioxide 3rd response **Surface Treatment:** Anodize **Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:** 

Straight thru

**Thread Series Designator:** 

Unjf all ends

Shelf Life:

N/a

## NSN 4820-00-953-9258

Check Valve - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.