NSN 4820-00-954-6012

Poppet Drain Cock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-954-6012 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** External seat for gasket seal (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 1st end Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 15000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end Material: Stainless steel flow control device **Material Specification:** Steel comp 440c national specification single material response flow control device Media For Which Designed: Air single response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unj 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-00-954-6012

Poppet Drain Cock - Page 2 of 2



Fiig:

A530c0

Mil-std (military Standard):

Mil-s-5002 spec.