NSN 4820-00-954-6012

Poppet Drain Cock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-954-6012

view Online at https://aerobasegroup.com/nsn/4820-00-954-6012
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
External seat for gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external boss 1st end
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
15000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Material:
Stainless steel flow control device
Material Specification:
Steel comp 440c national specification single material response flow control device
Media For Which Designed:
Air single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-00-954-6012

Poppet Drain Cock - Page 2 of 2

Fiig:

A530c0

Mil-std (military Standard):

Mil-s-5002 spec.

