NSN 4820-00-956-2497

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-956-2497

Pipe Size Accommodated:
1.000 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
197.0 gallons per minute
Maximum Operating Temp:
100.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
11-1/2 1st end
Maximum Operating Pressure:
2000.0 pounds per square inch single response
Thread Size:
1.000 inches 1st end
Opening Pressure Setting:
750.0 pounds per square inch
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-956-2497

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0