NSN 4820-00-956-5911

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-956-5911

Pipe Size Accommodated:
2.000 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing
Thready Qty Per Inch (tpi):
11-1/2 1st end
Maximum Operating Pressure:
Maximum Operating Pressure: 2500.0 pounds per square inch single response
2500.0 pounds per square inch single response
2500.0 pounds per square inch single response Thread Size:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
2500.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Material: Nickel alloy flow control device Media For Which Designed: Water-oil-gas single response Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: