## NSN 4820-00-956-5949

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-956-5949

Pipe Size Accommodated: 1.000 inches 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring Valve Discharge Flow Rate: 1188.0 pounds per hour Maximum Operating Temp: 450.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) 1st end Valve Operation Method: Automatic **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 11-1/2 2nd end Adjustable Pressure Range: +1.0/+300.0 pounds per square inch Maximum Operating Pressure: 300.0 pounds per square inch single response **Thread Size:** 1.000 inches 2nd end **Opening Pressure Setting:** 85.0 pounds per square inch Material: Stainless steel seat **Style Designator:** Err-090 **Thread Series Designator:** Npt 1st end Shelf Life:

N/a

## NSN 4820-00-956-5949

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

