NSN 4820-00-956-5957

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-956-5957

Pipe Size Accommodated:
1.000 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
6363.0 pounds per hour
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+1000.0/+5000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch single response
Thread Size:
1.000 inches 1st end
Opening Pressure Setting:
1145.0 pounds per square inch
Material:
Stainless steel stem
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-956-5957

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0