## NSN 4820-00-956-6181

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-956-6181

Pipe Size Accommodated:
2.000 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Connection Style:
G9 plain, optional en (pipe) 2nd end
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
11-1/2 2nd end
Maximum Operating Pressure:
Maximum Operating Pressure:  1300.0 pounds per square inch single response
1300.0 pounds per square inch single response
1300.0 pounds per square inch single response  Thread Size:
1300.0 pounds per square inch single response  Thread Size: 2.000 inches 1st end
1300.0 pounds per square inch single response  Thread Size: 2.000 inches 1st end  Opening Pressure Setting:
1300.0 pounds per square inch single response  Thread Size: 2.000 inches 1st end  Opening Pressure Setting: 750.0 pounds per square inch
1300.0 pounds per square inch single response  Thread Size: 2.000 inches 1st end  Opening Pressure Setting: 750.0 pounds per square inch  Material:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
1300.0 pounds per square inch single response Thread Size: 2.000 inches 1st end Opening Pressure Setting: 750.0 pounds per square inch Material: Copper alloy Style Designator: Err-090 Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: