

View Online at <https://aerobasegroup.com/nsn/4820-00-957-5549>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

450.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Valve Size:

4.000 inches

Maximum Operating Pressure:

500.0 pounds per square inch 2nd response

Outside Diameter:

10.000 inches 1st end

Face To Face Distance:

14.000 inches

Thickness:

1.250 inches 1st end

Bolt Hole Diameter:

0.875 inches 1st end

Bolt Circle Diameter:

7.875 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

6.938 inches 1st end

Material:

Iron body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0