## NSN 4820-00-958-3763

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-958-3763

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
G46b plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
4.0 pounds per square inch
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-958-3763

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0