NSN 4820-00-959-7299

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-959-7299

Pipe Size Accommodated:
2.000 inches 1st end
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
G9 plain, optional en (pipe) all ends
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded internal pipe all ends
Features Provided:
Valve stem lock shield and bonnet packing
Maximum Operating Pressure:
160.0 pounds per square inch single response
Thread Size:
2.000 inches all ends
Opening Pressure Setting:
30.0 pounds per square inch
Special Features:
W/diaphragm seal of bonnet cavity
Material:
Copper alloy 836 seat
Material Specification:
Qq-c-390, alloy b5/d federal specification single material response seat
Media For Which Designed:
Water, fresh 2nd response
Style Designator:
Err-090
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

NSN 4820-00-959-7299

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0