NSN 4820-00-961-5595



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-961-5595 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit 2nd response **Connection Style:** G45 flareless (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends Thready Qty Per Inch (tpi): 16 1st end **Maximum Operating Pressure:** 2500.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 12.0 degrees all ends **Opening Pressure Setting:** 145.0 pounds per square inch Material: Stainless steel Media For Which Designed: Ammonia, liquid 4th response **Style Designator:** Err-090 **Test Data Document:** 18876-9176158 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unjf all ends Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 4820-00-961-5595

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0