## NSN 4820-00-961-5595

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-961-5595

Thread Class:	
3a all ends	
Thread Direction:	
Right-hand all ends	
Flow Control Device:	
Poppet	
Disk Loading Method:	
Spring	
Maximum Operating Temp:	
275.0 degrees fahrenheit 2nd response	
Connection Style:	
G45 flareless (tube) all ends	
Valve Operation Method:	
Automatic	
Connection Type:	
Threaded external tube all ends	
Thready Qty Per Inch (tpi):	
16 1st end	
Maximum Operating Pressure:	
2500.0 pounds per square inch single response	
Thread Size:	
0.750 inches all ends	
Seat Angle:	
12.0 degrees all ends	
Opening Pressure Setting:	
145.0 pounds per square inch	
Material:	
Stainless steel	
Media For Which Designed:	
Ammonia, liquid 4th response	
Style Designator:	
Err-090	
Test Data Document:	
18876-9176158 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer draw	ving, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Thread Series Designator:	
Unjf all ends	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 4820-00-961-5595

Safety Relief Valve - Page 2 of 2

**Fiig:** A046b0

