NSN 4820-00-964-1936

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-964-1936

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
32.0 gallons per minute
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
G4 gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Valve stem lock shield and pressure tight outlet side
Thready Qty Per Inch (tpi):
12 all ends
Adjustable Pressure Range:
+500.0/+1400.0 pounds per square inch
Maximum Operating Pressure:
1400.0 pounds per square inch single response
Thread Size:
1.062 inches all ends
Material:
Steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Un all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4820-00-964-1936

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

