## NSN 4820-00-965-1210

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-965-1210

| Pipe Size Accommodated:                       |
|---|
| 1.250 inches 2nd end                          |
| Flow Control Device:                          |
| Disk  |
| Bonnet Type:                                  |
| Exposed spring                                |
| Bonnet Attachment Method:                     |
| Bolted  |
| Disk Loading Method:                          |
| Spring  |
| Renewable Seat Ring Type:                     |
| Threaded                                      |
| Connection Style:                             |
| Socket err-100                                |
| Valve Operation Method:                       |
| Automatic                                     |
| Connection Type:                              |
| Unthreaded internal pipe 2nd end              |
| Features Provided:                            |
| Pressure tight outlet side                    |
| Adjustable Pressure Range:                    |
| +300.0/+500.0 pounds per square inch          |
| Maximum Operating Pressure:                   |
| 4000.0 pounds per square inch single response |
| Material:                                     |
| Steel comp 303 flow control device            |
| Media For Which Designed:                     |
| Air single response                           |
| Style Designator:                             |
| Err-090                                       |
| Furnished Items And Quantity:                 |
| 2 nut and 1 wrench                            |
| Specification Or Standard:                    |
| A1 type and c class                           |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
| _   |
| Demilitarization:                             |
| No  |
| Fiig:   |
| A046b0  |

## NSN 4820-00-965-1210

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-v-22549 spec.