

View Online at <https://aerobasegroup.com/nsn/4820-00-965-1215>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Threaded

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

2950.0 cubic feet per minute

**Maximum Operating Temp:**

300.0 degrees fahrenheit single response

**Connection Style:**

G9 plain, optional en (pipe) all ends

**Valve Operation Method:**

Automatic or manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Valve stem lock shield

**Adjustable Pressure Range:**

+4101.0/+5000.0 pounds per square inch

**Maximum Operating Pressure:**

5000.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Material:**

Stainless steel seat

**Media For Which Designed:**

Gas, inert 2nd response

**Style Designator:**

Err-090

**Thread Series Designator:**

Npt all ends

**Reference Number Differentiating Characteristics:**

As differentiated by relief pressure range and valve size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0